

# DURAVAC

**DURAVAC PRODUCTS LIMITED**  
UNIT 170 JOHN WILSON BUSINESS PARK  
WHITSTABLE, KENT, CT5 3RA  
TEL:01227 770828 -FAX:01227 770878  
Email: [sales@duravac.co.uk](mailto:sales@duravac.co.uk)

## DURAVAC TW100 / TW100A MECHANICAL PUMP OIL

A Fully saturated paraffinic oil obtained by hydrotreating, the absence of unsaturated components results in a thermally and chemically stable product. Suitable for the majority of all major manufacturers pumps. Available with antioxidant (TW100A, slightly tinted) or without (TW100). The antioxidant increases lifetime of the oil.

### TYPICAL CHARACTERISTICS

<b>Saturated Vapour Pressure @ 20°C</b>	5.0 X 10 <sup>-9</sup> torr
<b>Average Boiling Range @ 5.0 X 10<sup>-1</sup> torr</b>	-
<b>Mid Range Boiling @ 5.0 X 10<sup>-1</sup> torr</b>	-
<b>Initial Boiling Point @ 5.0 X 10<sup>-1</sup> torr</b>	195°C
<b>Molecular Weight (typical)</b>	-
<b>Flash Point C.o.C</b>	>230°C
<b>Viscosity @ 40°C Nominal</b>	100 cst
<b>Pour point</b>	-18°C
<b>Specific Gravity @ 20°C (Typical):</b>	0.86
<b>Colour</b>	White / Slight tint
<b>Oil Type</b>	Mineral